

Industrial Tine Grapple

Specifications

Model	66"	72"	78"	86"
Overall Bucket Width	66.75"	72"	79"	86"
Depth of Bucket	38"	38"	38"	38"
Height of Bucket Back	22"	22"	22"	22"
Height w/ Grapple closed	31.5"	31.5"	31.5"	31.5"
Overall Grapple Width	61"	67"	67"	67"
Grapple Width Each	21.5"	21.5"	21.5"	21.5"
Grapple Opening	38"	38"	38"	38"
Approximate Weight	975#	1025#	1075#	1125#
Tine Spacing	5.25"	5.25"	5.25"	5.25"
No. Of Replaceable Tines	9	10	11	12
Usable Tine Length	30"	30"	30"	30"
Tine Size (1045 Material)	1.75"	1.75"	1.75"	1.75"
Cylinder Specifications				
Bore	2.5"	2.5"	2.5"	2.5"
Stroke	10"	10"	10"	10"
Rod Diameter	1.25"	1.25"	1.25"	1.25"
Cylinder Pin Size	1"	1"	1"	1"
Grapple Pivot Pin Size	1.25"	1.25"	1.25"	1.25"
Hydraulic Hoses 4500 PSI				
Nylon Hose Protector Sleeves				

- Designed to be used on skid steer loaders with 1300 lb (589 kg) or more lifting capacity.
- Specifications and designs are subject to change without notice.

Your TMW Dealer:



Attachments

320-453-3525

522 Meeker Ave. E.

Eden Valley, MN 55329