

Inverted Wood Splitter

Specifications

| WSI 30 Wood Splitter | WSI 24 | WSI 30 |
|------------------------------|---------------|---------------|
| Model | | |
| Overall Width | 48" | 48" |
| Over all Legnth | 82 | 88" |
| Height | 20" | 20" |
| Weight | 680 | 720# |
| Splitter Opening | 24 | 30" |
| Power Rating | | |
| 2000 PSI | 14 Ton | 20 Ton |
| 2500 PSI | 17 Ton | 25 Ton |
| 3000 PSI | 20 Ton | 30 Ton |
| 3500 PSI | 24 Ton | 35 Ton |
| Cycle Time WSI 24 | | |
| 10 Sec. @ 20 GPM | | |
| Cycle Time WSI 30 | | |
| 12 Sec. @ 20 GPM | | |
| Hydraulic Specifications | | |
| Cylinder Bore | 4" | 5" |
| Cylinder Stroke | 24" | 30" |
| Rod Diameter | 1.25" | 2" |
| | | |
| Hydraulic Hoses 4500 PSI | | |
| Nylon Hose Protector Sleeves | | |

- Designed to be used on skid steer loaders with 1300 lb (589 kg) or more lifting capacity.
- Specifications and designs are subject to change without notice.

Your TMW Dealer:



Attachments

320-453-3525

522 Meeker Ave. E.

Eden Valley, MN 55329