TMW Post Driver Cat. II 3 Point Mount



Features

- Makes Driving Post Easy
- Low Profile Design
- Category II 3 Point Hitch Mount
- Other Mounts Available
- Drive Post up to 10 Feet Long
- Easy to Maintain
- Domed or Flat Head Tools
- 12 Month Warranty





522 Meeker Ave. E. • Eden Valley, MN 55329

Post Driver Specifications

Operating Weight1560 lbs.1695 lbs.Collapsed Height84 lnch84 lnchExtended Height167 lnch167 lnchMaximum Tool Height above Ground123 lnch123 lnchMinimum Tool Height above Ground37 lnch37 lnchMountingCat. II 3 Point HitchCat. II 3 Point HitchOther Mounts AvailableOther Mounts AvailableOther Mounts AvailableSticking Force (Blows per Minute)500-900 BPM400-800 BPMHydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 lnch3 lnchPost Driving Tool OD Diameter8 lnch9 lnchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree (Forward)15 Degree (Back)15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthAccessoriesPost Driving Tool DomedStandardPost Driving Tool DomedStandardOptional	Model	PD1600T	PD1850T
Extended Height167 Inch167 InchMaximum Tool Height above Ground123 Inch123 InchMinimum Tool Height above Ground37 Inch37 InchMountingCat. II 3 Point Hitch Other Mounts AvailableCat. II 3 Point Hitch Other Mounts AvailableSticking Force (Blows per Minute)500-900 BPM400-800 BPMHydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driver Rotate (Side to Side)25 Degree Right 25 Degree Left25 Degree Right 25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Back)Warranty12 Month12 MonthAccessoriesStandardStandard	Operating Weight	1560 lbs.	1695 lbs.
Maximum Tool Height above Ground123 Inch123 InchMinimum Tool Height above Ground37 Inch37 InchMountingCat. II 3 Point HitchCat. II 3 Point HitchOther Mounts AvailableOther Mounts AvailableSticking Force (Blows per Minute)500-900 BPM400-800 BPMHydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree (Forward)Post Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Back)Warranty12 Month12 MonthAccessoriesStandardStandard	Collapsed Height	84 Inch	84 Inch
Minimum Tool Height above Ground37 Inch37 InchMountingCat. II 3 Point HitchCat. II 3 Point HitchOther Mounts AvailableSticking Force (Blows per Minute)500-900 BPM400-800 BPMHydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree (Forward)15 Degree (Forward)Narranty12 Month12 MonthAccessories21 Month12 MonthPost Driving Tool DomedStandardStandard	Extended Height	167 Inch	167 Inch
MountingCat. II 3 Point Hitch Other Mounts AvailableCat. II 3 Point Hitch Other Mounts AvailableSticking Force (Blows per Minute)500-900 BPM400-800 BPMHydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree (Forward)15 Degree (Back)15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthAccessoriesStandardStandard	Maximum Tool Height above Ground	123 Inch	123 Inch
Other Mounts AvailableOther Mounts AvailableSticking Force (Blows per Minute)500-900 BPM400-800 BPMHydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree (Forward)Post Driver Tilt (Forward to Back)15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthAccessoriesStandardStandard	Minimum Tool Height above Ground	37 Inch	37 Inch
Sticking Force (Blows per Minute)500-900 BPM400-800 BPMHydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driving Tool ID Diameter7-1/8 Inch8-1/4 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Back)Warranty12 Month12 MonthAccessoriesPost Driving Tool DomedStandard	Mounting	Cat. II 3 Point Hitch	Cat. II 3 Point Hitch
Hydraulic Flow11-18 GPM13-24 GPMWorking Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driving Tool ID Diameter7-1/8 Inch8-1/4 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Back)Warranty12 Month12 MonthAccessoriesPost Driving Tool DomedStandard		Other Mounts Available	Other Mounts Available
Working Pressure2000PSI2200PSIWorking Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driving Tool ID Diameter7-1/8 Inch8-1/4 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree RightPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)Warranty12 Month12 MonthAccessoriesStandardStandard	Sticking Force (Blows per Minute)	500-900 BPM	400-800 BPM
Working Class750 (ft/lbs)1150 (ft/lbs)Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driving Tool ID Diameter7-1/8 Inch8-1/4 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree RightPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)Warranty12 Month12 MonthAccessoriesPost Driving Tool DomedStandard	Hydraulic Flow	11-18 GPM	13-24 GPM
Tool Shank Diameter2.7 Inch3 InchPost Driving Tool OD Diameter8 Inch9 InchPost Driving Tool ID Diameter7-1/8 Inch8-1/4 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)Warranty12 Month12 MonthAccessoriesStandard	Working Pressure	2000PSI	2200PSI
Post Driving Tool OD Diameter8 Inch9 InchPost Driving Tool ID Diameter7-1/8 Inch8-1/4 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)15 Degree (Back)15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthPost Driving Tool DomedStandard	Working Class	750 (ft/lbs)	1150 (ft/lbs)
Post Driving Tool ID Diameter7-1/8 Inch8-1/4 InchPost Driver Rotate (Side to Side)25 Degree Right25 Degree Right25 Degree Left25 Degree Left25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)Marranty12 Month12 MonthAccessoriesPost Driving Tool DomedStandard	Tool Shank Diameter	2.7 Inch	3 Inch
Post Driver Rotate (Side to Side)25 Degree Right 25 Degree Left25 Degree Right 25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)15 Degree (Back)15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthAccessoriesStandardStandard	Post Driving Tool OD Diameter	8 Inch	9 Inch
25 Degree Left25 Degree LeftPost Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)15 Degree (Back)15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthAccessoriesStandardStandard	Post Driving Tool ID Diameter	7-1/8 Inch	8-1/4 Inch
Post Driver Tilt (Forward to Back)15 Degree (Forward)15 Degree (Forward)15 Degree (Back)15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthAccessoriesStandardStandard	Post Driver Rotate (Side to Side)	25 Degree Right	25 Degree Right
15 Degree (Back)15 Degree (Back)Warranty12 Month12 MonthAccessoriesPost Driving Tool DomedStandardStandard		25 Degree Left	25 Degree Left
Warranty 12 Month 12 Month Accessories Control Domed Standard Post Driving Tool Domed Standard Standard	Post Driver Tilt (Forward to Back)	15 Degree (Forward)	15 Degree (Forward)
Accessories Post Driving Tool Domed Standard		15 Degree (Back)	15 Degree (Back)
Post Driving Tool Domed Standard Standard	Warranty	12 Month	12 Month
5	Accessories		
Post Driving Tool Flat Optional Optional	Post Driving Tool Domed	Standard	Standard
	Post Driving Tool Flat	Optional	Optional



Your TMW Dealer

